

SPECS.

| TYPE | CAPACITY | LENGTH | WIDTH mm | WIDTH mm | HEIGHT mm | WEIGHT mm |
|----------------|----------|--------|----------|-----------|-----------|-----------|
| SINGLE AUGER | m3 | mm | 2 DOORS | CONVEYOR | | |
| V-MIX 8 | 8m3 | 4930 | 2200 | 2030/2250 | 2690 | 3250 |
| V-MIX 10 (h8) | 10m3 | 5130 | 2200 | 2030/2250 | 2990 | 3600 |
| V-MIX 10 (n12) | 10m3 | 5190 | 2560 | 2330 | 2690 | 3970 |
| V-MIX 12 | 12m3 | 5390 | 2560 | 2330 | 2990 | 4200 |
| V-MIX 15 | 15m3 | 6250 | 2999 | 2800 | 2600 | 5370 |
| V-MIX 18 | 18m3 | 6400 | 2999 | 2800 | 2900 | 6000 |

| DOUBLE AUGER | | | | | | |
|--------------|------|------|------|-----------|-----------|------|
| V-MIX 16 | 16m3 | 7100 | 2200 | 2030/2250 | 2030/2250 | 2650 |
| V-MIX 20 | 20m3 | 7400 | 2560 | 2330 | 2330 | 2650 |
| V-MIX 24 | 24m3 | 7600 | 2560 | 2330 | 2330 | 2690 |

| TYPE | MAX LOAD | TYRES | DISCHARGE | DISCHARGE | POWER | POWER |
|----------------|----------|-----------------|-----------|-----------|-------------|-----------------|
| SINGLE AUGER | kgs | | DOORS | CONVEYOR | REQUIREMENT | REQUIREMENT |
| | | | HEIGHT mm | HEIGHT mm | hp | REDUCTION DRIVE |
| V-MIX 8 | 3500 | 400/60x15.5 | 810 | 675 | 60 | 40 |
| V-MIX 10 (h8) | 4300 | 400/60x15.5 | 810 | 675 | 75 | 55 |
| V-MIX 10 (n12) | 4300 | 400/60x15.5 | 810 | 675 | 75 | 55 |
| V-MIX 12 | 5000 | 400/60x15.5 | 810 | 675 | 80 | 60 |
| V-MIX 15 | 6300 | TWIN215/75R17.5 | 810 | 675 | 100 | 75 |
| V-MIX 18 | 7500 | TWIN215/75R17.5 | 810 | 675 | 120 | 90 |

| DOUBLE AUGER | | | | | | |
|--------------|------|-----------------|-----|-----|-----|----|
| V-MIX 16 | 7000 | TWIN215/75R17.5 | 840 | 705 | 100 | 75 |
| V-MIX 20 | 7350 | TWIN215/75R17.5 | 840 | 705 | 120 | 90 |
| V-MIX 24 | 7800 | TWIN215/75R17.5 | 840 | 705 | 130 | 95 |

| TYPE | CAPACITY | LENGTH | WIDTH | HEIGHT | WEIGHT | MAX LOAD | TYRES | POWER | POWER |
|-----------------|----------|--------|---------|--------|--------|----------|-------------|-------------|-----------------|
| SINGLE AUGER | m3 | mm | 2 DOORS | mm | mm | kgs | | REQUIREMENT | REQUIREMENT |
| LOW LOADER | | | mm | | | | | hp | REDUCTION DRIVE |
| V-MIX 8T | 8m3 | 5830 | 2200 | 2280 | 3330 | 3500 | 215/75R17.5 | 60 | 40 |
| V-MIX 10T (h8) | 10m3 | 5830 | 2200 | 2580 | 4300 | 4300 | 215/75R17.5 | 75 | 55 |
| V-MIX 10T (n12) | 10m3 | 5830 | 2560 | 2280 | 4300 | 4300 | 215/75R17.5 | 75 | 55 |
| V-MIX 12T | 12m3 | 5830 | 2560 | 2650 | 5000 | 5000 | 215/75R17.5 | 80 | 60 |

REGIONAL IMPORTER/DEALER



GERMANY
 Maschinenfabrik
 Bernard van Lengerich GmbH & Co.
 D-48486 Ernsburen
 Telephone: 0049 5903 951 47
 Fax: 0049 5903 951 34
 Email: bvl-van-lengerich@t-online.de

UK
 BvL UK
 51 Leam Terrace
 Leamington Spa
 CV31 1DG
 Phone/Fax: 01926 315079
 Email: bvluk@targettraining.co.uk

DENMARK
 FLEX AGRO A/S
 Hvidemollevej 9-11
 8900 Randers
 Phone: 08914 14 44
 Fax: 08914 12 45
 Email: ple.flexagro@hf-c.dk



V-MIX8 with front cross conveyor



V-MIX15 on standard twin wheels

HANDLES ALL FEED STUFFS
 CHOPS AND MIXES ROUND BALES
 SPECIAL AUGER DESIGN
 PRODUCES SUPERB FEED RATION
 DISCHARGE SOLUTIONS TO SUIT

- side doors
- conveyors
- elevators

PROGRAMMABLE WEIGH SYSTEM
 COUNTER KNIVES
 LOW-LOADER MODELS
 SIMPLE MAINTENANCE
 GERMAN PRECISION ENGINEERING



V-MIX10 loading minerals / straights

V-MIX12T low-loader model



V-MIX18 - single auger & gearbox



V-MIX20 twin auger model



Straw bale added to be chopped & mixed by V-MIX10



Inside conveyor - same rubber belt on elevator

van Lengerich



Here the V-MIX has turned a round straw bale and some precision chopped grass silage into a superbly chopped and mixed TMR. As a result, no selective feeding is possible and full nutritional benefit is achievable.



VERTICAL DIET FEEDER/MIXER WAGON
 QUALITY THROUGH CONTROL